AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings of claims in the application:

LISTING OF CLAIMS:

an acid-base mixture, the mixture comprising a base component and an acid component, wherein[[:]] the base component comprises 2-ethyl-4-methylimidazole and 4-methylimidazole, and optionally 2-ethylimidazole, and the acid-base mixture is ion conductive and has an ion conductivity of 10⁻⁴ Scm⁻¹ or higher at 100°C.

2. (cancelled)

- 3. (currently amended) The <u>ion conductor comprising</u> an acid-base mixture according to claim 1, having a melting point of 120°C or lower or no melting point.
- 4. (currently amended) The <u>ion conductor comprising</u>
 an acid-base mixture according to claim 1, being an equimolar mixture of the base component and the acid component.

5. (currently amended) The <u>ion conductor comprising</u>
<u>an</u> acid-base mixture according to claim 1, being liquid at room temperature.

6-8. (cancelled)

- 9. (currently amended) The <u>ion conductor comprising</u> an acid-base mixture according to claim 1, wherein at least one of the acid components comprises an acid structurally free from a fluorine atom.
- 10. (currently amended) The ion conductor comprising an acid-base mixture according to claim 1, wherein at least one of the acid components comprises an inorganic acid.
- 11. (currently amended) The <u>ion conductor comprising</u> an acid-base mixture according to claim 10, wherein at least one of the acid components comprises sulfuric acid or phosphoric acid.

12. (cancelled)

13. (currently amended) The $\underline{\text{ion conductor comprising}}$ $\underline{\text{an}}$ acid-base mixture according to claim 1, being proton conductive.

14-25. (cancelled)

- 26. (withdrawn and currently amended) The ion conductor comprising an acid-base mixture according to claim 14 1, which comprises an electrolyte in a fuel cell, a secondary batter battery, an electric double layer capacitor, or an electrolytic capacitor.
- 27. (withdrawn and currently amended) A fuel cell, a secondary batter battery, an electric double layer capacitor, or an electrolytic capacitor comprising an ion conductor as an electrolyte, said ion conductor comprising an acid-base mixture comprising a base component and an acid component,

wherein the base component comprises 2-ethyl-4-methylimidazole and 4-methylimidazole, and optionally 2-ethylimidazole, and

said ion conductor has a melting point of $120\,^{\circ}\mathrm{C}$ or lower or no melting point, and a glass transition temperature of $25\,^{\circ}\mathrm{C}$ or lower.

28. (cancelled)

Docket No. 8007-1102 Appln. No. 10/561,519

- 29. (new) The ion conductor according to claim 1, wherein the molar ratio of 2-ethyl-4-methylimidazole:4-methylimidazole is 1:1.
- **30. (new)** The ion conductor according to claim 1, wherein the amount of optional 2-ethylimidazole is 90% by weight or less of the base component.
- **31. (new)** The ion conductor according to claim 1, wherein the molar ratio of base component to acid component ranges from 99:1 to 1:99.
- 32. (new) The ion conductor according to claim 1, wherein the ion conductor has a melting point of 120°C or lower and a glass transition temperature of 25°C or lower.